

UT275 TELUROMETRO DE PINZA



Professional earth clamp meter with build-in leakage meter UNI-T UT275

Safety Rating

CAT III 300V

Certifications

CE

EN:61010-1

EN:61326-1

EN:61010-2-032

Specifications

Earth Ground Resistance

0.01~0.099Ohm $\pm(1\%+0.01)$

0.1~0.99Ohm $\pm(1\%+0.01)$

1.0~49.9Ohm $\pm(1.5\%+0.1)$

50.0~99.5Ohm $\pm(2\%+0.5)$

100~199Ohm $\pm(3\%+1)$

200~395Ohm $\pm(10\%+5)$

400~590Ohm $\pm(20\%+10)$

600~1000Ohm $\pm(25\%+20)$

Leakage Current

0.00~299mA $\pm(2.5\%+2mA)$

0.30~2.99A $\pm(2.5\%+100mA)$

3.00~30.0A $\pm(2.5\%+300mA)$

Features

Display Count 9999
Auto Range
Jaw Capacity 28mm
Auto Power Off
Low Battery Indication 5.2V
Data Hold
Data Logging 30
Data Recall
LCD Backlight
Auto Calibration
Resistance Limit Alarm

General Characteristic

Power 1.5V Alkaline Batteries(LR6)×4
LCD Size 47mm X 28.5 mm
Product Color Red and Grey
Product Net Weight 1320g
Product Size 293mm X 90mm X66 mm
Standard Accessories Batteries, Test Ring, Tool Box, Gift Box,
English Manual